

Upright All Glass Display Refrigerated Cabinets



GET IN TOUCH

info@primsal.com primsal.com

Environmentally Friendly - Make the smart switch



Upright All Glass Display Refrigerated Cabinet

PRDC478UC

Capacity (L)	78L
TDA	0.8 m ²
TEC (kWh/24h)	2.76kwh/24h
EEL	16.85
Energy Rating	8 stars
Outer material	Glass
Door	Tempered Glass Door
Temperature range (°C)	+2 to +10 °C
Cooling System	Ventilated
Thermostat	Digital
Compressor	Huayi
Condenser	Bondi pipe
Refrigerant	R600a 45g
Voltage/Frequency	220-240V~、 50Hz
Defrost	Automatic
Light	LED
Input Power	200W
Shelves	4
Shelves Holder	Stainless steel
Wheels	Feet
NW (kg)	37



GET IN TOUCH

info@primsal.com primsal.com

Environmentally Friendly - Make the smart switch



Upright All Glass Display Refrigerated Cabinet

PRDC498UC

Capacity (L)	98L
TDA	1.01 m ²
TEC (kWh/24h)	3.34kWh/24h
EEL	18.26
Energy Rating	8 stars
Outer material	Glass
Door	Tempered Glass Door
Temperature range (°C)	+2 to +10 °C
Cooling System	Ventilated
Thermostat	Digital
Compressor	Huayi
Condenser	Bondi pipe
Refrigerant	R600a 45g
Voltage/Frequency	220-240V~、 50Hz
Defrost	Automatic
Light	LED
Input Power	200W
Shelves	4
Shelves Holder	Stainless steel
Wheels	Feet
NW (kg)	41.5



GET IN TOUCH

info@primsal.com primsal.com

Environmentally Friendly - Make the smart switch



Upright All Glass Display Refrigerated Cabinet

PRDC4238UC

Capacity (L)	238L
TDA	1.77 m ²
TEC (kWh/24h)	3.99kwh/24h
EEL	15.83
Energy Rating	9 stars
Outer material	Glass
Door	Tempered Glass Door
Temperature range (°C)	+2 to +10 °C
Cooling System	Ventilated
Thermostat	Digital
Compressor	Cubigel
Condenser	Bondi pipe
Refrigerant	R290 55g
Voltage/Frequency	220-240V~、 50Hz
Defrost	Automatic
Light	LED
Input Power	340W
Shelves	5
Shelves Holder	Stainless steel
Wheels	Universal Wheels
NW (kg)	81



GET IN TOUCH

info@primsal.com primsal.com

Environmentally Friendly - Make the smart switch



Upright All Glass Display Refrigerated Cabinet

PRDC4278UC

Capacity (L)	278L
TDA	2.08 m ²
TEC (kWh/24h)	3.84kWh/24h
EEL	13.7
Energy Rating	9 stars
Outer material	Glass
Door	Tempered Glass Door
Temperature range (°C)	+2 to +10 °C
Cooling System	Ventilated
Thermostat	Digital
Compressor	Cubigel
Condenser	Bondi pipe
Refrigerant	R290 70g
Voltage/Frequency	220-240V~、 50Hz
Defrost	Automatic
Light	LED
Input Power	340W
Shelves	5
Shelves Holder	Stainless steel
Wheels	Universal Wheels
NW (kg)	94



GET IN TOUCH

info@primsal.com primsal.com

Environmentally Friendly - Make the smart switch

